

Impregnator no. 5

Presentation

Fields of use:

Protection of interior and exterior walls and floors

Composition:

Impregnator in aqueous phase

Properties:

Transparent, non-yellowing, regulates slightly sandy and very porous substrates.
Highly water- and soiling-resistant.

Packing:

1 L and 5 L

Application

Substrate and substrate preparation:

Concrete, mortar, dry mineral coatings

Preparation:

Thinning: None for Smooth finish mortar porous substrates.

Add 50% water for less porous substrates like Interior self-levelling mortar or Smooth finish mortar with very close finish.

Application conditions:

Temperature	10-30°C
Relative humidity	<80%
Protect from wind, sun and frost during application and setting	

Application equipment:

Microfibre roller, gun

Application method:

Shake before use.

Apply until saturated (normally two coats) in criss-cross pattern.

Coverage:

Approximately 10 m² per litre in two coats (depends on the porosity of the substrate)

Drying time at 20°C and 60% relative humidity:

Between coats	Approximately 6 hours (depends on the porosity of the substrate)
Complete drying	24 hours minimum. Do not varnish before 24 hours

Tool cleaning:

Water

Technical characteristics and performances

Product appearance:

Appearance in the pot: milky liquid

Finished appearance: satin-finish colourless, transparent film

Density A+B (at 20°C): 1.0 +/-0.1

Flash point: N/A

Practical duration of use: N/A

Other data: -

Storage and safety

1 year shelf life in its unopened original packaging, away from sunlight or freezing, at a temperature of between +5° and 35°C.

Check the best-before-date on the packaging before use.

For additional safety information, consult the safety data sheet.

All the information in this technical sheet is given for information only and shall not incur our responsibility. Always test products before use.

Refer to the safety data sheet for any additional information on use precautions and safety instructions.