

## Matt finish natural plant-based primer and paint

### Presentation

**Areas of use:** Matt natural primer and paint is intended for substrate priming and interior wall decoration, offering a matt finish.

**Composition:** Plant oil and mineral based aqueous dispersion.

**Properties:** Rich in recyclable raw materials, offering an ecologically sound habitat and improved air quality. Solvent and cosolvent free. Microporous and lightly washable. Easy to apply, offering excellent opacity and covering qualities. Regulates substrate porosity.

**Packaging:** 2.5L and 10L

### Application

#### Substrate and substrate preparation:

On new substrates, lightly sand and remove dust before application.

On new concrete or cement, wait 45 days in order for the pH to fall below 9.

On painted substrates, wash if necessary, rinse and allow to dry. Then sand before application.

#### Application conditions:

Before application, check the moisture level of the substrate (4% maximum humidity).

Temperature	>10°C and <35°C (ideal temperature: >15°C and <20°C)
Relative humidity	<65% (fair weather)

#### Application tools:

Synthetic bristle paint brush

Microfibre roller (6 mm: smooth finish or 10 mm: textured finish)

Paint sprayer: dilute with between 8 to 10% water and 5 to 8% water and apply with airless paint sprayer (0,43 mm or 0,38 mm nozzle)

#### Application method:

Mix thoroughly before use.

Apply a coat of natural primer in white, then two coats of white or coloured matt natural paint.

The white natural primer should also be applied before the application of matt and satin natural lacquers.

#### Consumption:

150 microns per coat - 8 to 10 sqm per litre

#### Drying times at 20°C with 60% relative humidity:

Dry to the touch	1 hour
Between coats	6 hours
Fully dry	3 days, with full mechanical resistance after 10 days

**Tool cleaning:** Water

#### Technical features

**Density (at 20°C):** Approximately 1.5

#### Additional data:

Application warning: frost sensitive

#### Storage and safety

12 months in the original, unopened packaging, away from direct sunlight and frost, at a temperature between +5° and 35°C.

For further information concerning safety, please consult the Safety Information Sheet.

*The information given in this technical sheet is an indication only and cannot be used to hold Marius Aurenti in any way responsible. Please carry out product tests on a small area before proceeding.  
For all further information concerning product use and security, please refer to the Safety Information Sheet.*